

Vermeer®

Mini Skid Steers

S600/S600TX



Mini Skid Steers

S600/S600TX

There's nothing mini about their productivity

From landscape contractors to do-it-yourselfers, the Vermeer mini skid steer is a machine built for multiple applications, a machine that saves time-intensive labor, a machine that's backed by a strong dealer network. We know because we asked customers exactly what features they wanted in a mini skid steer. And when our customers talk, we listen.

The result is the S600 and S600TX, two machines built with Vermeer quality in mind. Ideal for a wide range of applications, these mini skid steers maneuver easily around tough worksites and reduce workloads in the process.

In addition to the standard 1-year / 1000-hour limited warranty, the S600 and S600TX come with the only structural warranty in the mini skid steer industry: 3 years or 3000 hours on the mainframe and boom loader arms.

Available with a 30 hp (22.4 kW) gas engine or 25 hp (18.6 kW) diesel engine.

Take control, stand tall, and ride in comfort and safety



Transport and boom bucket motion are controlled by two ergonomically designed joysticks. The handgrip is positioned to help improve operator balance while on uneven terrain.



Ground drive is controlled by a single joystick, giving the operator a smooth range of motion.



The ride-on unit comes with a spring-cushioned platform, keeping the operator out of mud and debris. At 14.5" (36.8 cm), it is high enough to enhance visibility while providing clearance for backing over curbs.



Cushions are positioned in front and on either side of the operator, increasing comfort and decreasing the chance of injury when driving over uneven terrain.

Vermeer®



Plug it in, hook it up, and make fewer pit stops



The standard auxiliary 12-volt power port lets operators power a temporary light kit or other attachments without having to tap into the unit's existing wire harness.



Curved loader arms lift up and away from the machine, providing better height and reach for loading and unloading. This also provides the clearance necessary to avoid damaging the front of the machine when using large-diameter augers and allows an operator to dump a bucket into the center of a one-ton truck.



A universal mounting plate makes it easier for the operator to hook up various attachments.



With a 15-gal (56.8 L) fuel tank, the S600 and S600TX boast the largest tank capacity in their class, eliminating the need for refueling during the typical workday. The 14-gal (53 L) hydraulic tank is also the largest of its class, enhancing the life of the hydrostatic system by increasing dwell time of the hydraulic fluid.

Attachments

Thanks to our wide range of attachments, Vermeer mini skid steers can be used in a multitude of applications. With universal mounting plates, it's easy to hook up a tool and get right back on the job.



Vermeer understands how choosing the right attachment for your mini skid steer can impact your bottom line. Your local Vermeer dealer can help you select the attachment best suited for your projects.



Land Leveler

49" (124.5 cm) wide
170 lb (77.1 kg)



Tooth Bucket

4 cu ft (.1 cu m), 42" (106.7 cm) wide
182 lb (82.6 kg)



Tree Forks

24.5" (62.2 cm) wide
45" (114.3 cm) long
169 lb (76.7 kg)



Rock Bucket

4 cu ft (.1 cu m), 42" (106.7 cm) wide
166 lb (75.3 kg)



Forged Forks

30" (76.2 cm), adjustable width
32" (81.3 cm) long
162 lb (73.5 kg)



4-in-1 Bucket

5 cu ft (.1 cu m), 42.5" (108 cm) wide
268 lb (121.6 kg)



Standard Bucket

4 cu ft (.1 cu m), 42" (107 cm) wide, 169 lb (76.7 kg); 6 cu ft (.2 cu m), 48" (121.9 cm) wide, 214 lb (97.1 kg)
Mini-tilt attachment: 60 lb (27.2 kg)



Sweeper Bucket

42" (106.7 cm) wide
375 lb (170.1 kg)



Other Buckets Available

Narrow bucket: 34.5" (87.6 cm)
Light material /
High capacity: 48" (121.9 cm)

Scrap Grapple Bucket

36" (91.4 cm) wide, 315 lb (142.9 kg)
42" (106.7 cm) wide, 335 lb (152 kg)



Root Cutter

14" (35.6 cm) depth
550 lb (249.5 kg)



Brush Grapple

36" (91.4 cm) wide, 225 lb (102.1 kg)
42" (106.7 cm) wide, 245 lb (111.1 kg)



Hydraulic Boring Attachment

25" (63.5 cm) wide
115 lb (52.2 kg)



Log Grapple

34" (86.4 cm) wide
42" (106.7 cm) wide
285 lb (129.3 kg)
3-position inline, 45° and 90°



Vibratory Plow

Up to 12" (30.5 cm) plow depth
340 lb (154.2 kg)



Dozer Blade

47" (120 cm) wide, 120 lb (54.4 kg)

Dozer Blade with Optional Tilt

47.8" (121.4 cm) wide, 120 lb (54.4 kg)



Snow Blower

48" (121.9 cm) wide, 57" (144.8 cm) high
14" (35.6 cm) auger diameter
490 lb (222.3 kg)



Power Shovel

32" (81.3 cm) wide
162 lb (73.5 kg)



Tiller

51" (129.5 cm) wide
4.5" (11.4 cm) deep
256 lb (116.1 kg)



Auger Drive, High-Speed

13 gpm (49.2 L/min), 85 rpm, 154 lb (69.9 kg)

Auger Drive, High-Torque

13 gpm (49.2 L/min), 68 rpm, 154 lb (69.9 kg)

Auger Accessories

Standard bit: 6" (15.2 cm), 9" (22.9 cm),
12" (30.5 cm), 15" (38.1 cm), 18" (45.7 cm),
24" (61 cm), 30" (76.2 cm), 36" (91.4 cm)
Rock bit: 9" (22.9 cm)
HTF bit: 30" (76.2 cm); 36" (91.4 cm)
Max depth (without extensions): 54" (137.2 cm)
Auger extension: 12" (30.5 cm)



Mini Sod Roller / Unroller

50" (127 cm) wide
160 lb (72.6 kg) empty



Hydraulic Hammer

1.8" (4.6 cm) diameter
850 – 1250 bpm impact frequency
180 energy class
180 lb (81.7 kg)



Auger Trench Backfill Attachment

52" (132.1 cm) wide
270 lb (122.5 kg)



Harley Power Rake

58" (147.3 cm) wide
485 lb (220 kg)
Swing: manual or hydraulic



Rotary Broom, Manual Angle

42" (106.7 cm) wide, 400 lb (181.4 kg)
48" (121.9 cm) wide, 475 lb (215.5 kg)



Landscape Rake

40" (101.6 cm) wide
4.5" (11.4 cm) deep
460 lb (208.7 kg)



Standard Trencher

Trenches: 4 – 6" (10.2 to 15.2 cm) wide
and 24 – 48" (61 to 121.9 cm) deep



Multitask Tool

24" (61 cm) wide
120 lb (54.4 kg)
Includes jib pole



Special Features



- Turf-friendly tires or lug tires are available, depending on the worksite.



S600TX



- Choose 7" (17.8 cm) or optional 9" (22.9 cm) tracks to match the needs and job requirements of the customer.
- Attachments receive 13 gpm (49.2 L/min) of hydraulic flow for optimal power and efficiency.
- Sealed track roller bearings reduce daily maintenance by eliminating greasing.
- Scratch-resistant hydraulic lift cylinder rods help prevent rust.
- A hinged door in front of the machine allows easy access to the engine compartment, whether the boom is fully raised or lowered.



Specifications S600

S600TX

General		
Design type	Ride-on / Wheel-drive	Ride-on / Track-drive
Length with standard bucket	93" (236.2 cm)	93" (236.2 cm)
Length without bucket	71" (180.3 cm)	71" (180.3 cm)
Width with standard bucket	42" (106.7 cm)	42" (106.7 cm)
Width without bucket	40.5" (102.9 cm)	36" (91.4 cm)
Height (transport)	57.5" (146.1 cm)	57.5" (146.1 cm)
Height to hinge pin	80" (203.2 cm)	80" (203.2 cm)
Reach to hinge pin	22" (55.8 cm)	22" (55.8 cm)
Weight with standard bucket, gas engine	2270 lb (1029.7 kg)	2530 lb (1147.6 kg)
Weight with standard bucket, diesel engine	2515 lb (1140.8 kg)	2775 lb (1258.7 kg)
Weight without bucket, gas engine	2155 lb (977.5 kg)	2415 lb (1095.4 kg)
Weight without bucket, diesel engine	2400 lb (1088.6 kg)	2660 lb (1206.6 kg)
Ground clearance	5.75" (14.6 cm)	4.5" (11.4 cm)
Wheelbase	30.5" (77.5 cm)	N / A
Ground pressure (wide tracks)	N / A	4 psi (0.3 bar)
Ground pressure (narrow tracks)	N / A	5.5 psi (0.4 bar)
Width with tracks	N / A	36" (91.4 cm) with 7" (17.8 cm) / 40" (101.6 cm) with 9" (22.9 cm) tracks
Track width	N / A	7" (17.8 cm), 9" (22.9 cm) option
Track length	N / A	42" (106.7 cm) ground contact
Track type	N / A	Rubber
Engine (gas option)		
Make and model	Kohler Command Pro	Kohler Command Pro
Fuel type	Gas	Gas
Gross horsepower	30 hp (22.4 kW)	30 hp (22.4 kW)
Cooling system	Air	Air
Air cleaner	Heavy-duty dual element	Heavy-duty dual element
Fuel-tank capacity	15 gal (56.8 L)	15 gal (56.8 L)
Displacement	45.6 cu in (747 cm ³)	44.0 cu in (725.0 cm ³)
Number of cylinders	2	2
Max engine operating angle (left and right)	30°	30°
Torque (max @ 2400 rpm)	47.5 ft-lb (64.4 Nm)	N / A
Torque (max @ 2800 rpm)	N / A	39.1 ft-lb (54.1 Nm) @ 2800 rpm
Engine (diesel option)		
Make and model	Kubota D1105	Kubota D1105
Fuel type	Diesel	Diesel
Gross horsepower	25 hp (18.6 kW)	25 hp (18.6 kW)
Cooling system	Liquid	Liquid
Air cleaner	Heavy-duty dual element	Heavy-duty dual element
Fuel-tank capacity	15 gal (56.8 L)	15 gal (56.8 L)
Performance		
Rated operating capacity (SAE)	600 lb (272.1 kg)	500 lb (226.8 kg)
Tipping capacity (with operator)	1200 lb (544.3 kg)	1450 lb (657.7 kg)
Travel speed	4.4 mph (7.1 km/h)	4.5 mph (7.2 km/h)
Operation		
Steering	Single pilot-operated joystick	Single pilot-operated joystick
Number of track assemblies	N / A	2
Lift and curl	Single dual-axis joystick	Single dual-axis joystick
Transmission	Tandem hydrostatic pumps	Tandem hydrostatic pumps
Hydraulic System		
Auxiliary gpm @ 3000 rpm diesel; 3600 rpm gas	13.2 gpm (49 L/min)	13.2 gpm (49 L/min)
Auxiliary pump relief	3000 psi (206.8 bar)	3000 psi (206.8 bar)
Ground drive gpm @ 3000 rpm diesel; 3600 rpm gas	10.92 gpm (42.0 L/min)	11.23 gpm (43.2 L/min)
Operating pressure	3050 psi (210.3 bar)	3050 psi (210.3 bar)
Tank capacity	14 gal (53 L)	14 gal (53 L)
Hydraulic system capacity	16 gal (60.6 L)	16 gal (60.6 L)
Fittings	Quick coupler hydraulic fittings	Quick coupler hydraulic fittings
Electrical		
Battery	12-V operating system	12-V operating system
Boom		
	Dual cylinder lift	Dual cylinder lift
	Standard mounting plate with quick attach	Standard mounting plate with quick attach
Safety Features		
	Boom lockout arm	Boom lockout arm
	Operator presence in platform	Operator presence in platform
	Console cushions	Console cushions
	Hydraulic parking brake	Hydraulic parking brake

The Vermeer dealer network: Reliable support, all over the world.



With nearly 200 locations across the globe - you're never far from an independent, authorized Vermeer dealer. Our dealers are in place to support your success with product expertise that's second to none.



When you need service, you can count on your local Vermeer dealer. With multiple locations, remote service trucks, and factory-offered technician training, your local Vermeer dealer offers reliable service that keeps your equipment running.



Vermeer parts are designed and manufactured to original specifications, so whether they're new parts or replacement parts, they'll live up to the Vermeer name.



Vermeer EMEA
(Europe, Middle East, Africa and CIS)
P.O. Box 323
4460 AS Goes
the Netherlands
Phone: +31 113 272700
Fax: +31 113 272727

Vermeer Corporation
1210 Vermeer Road East
P.O. Box 200
Pella, Iowa 50219 U.S.A.
Phone: (641) 628-3141
Fax: (641) 621-7773
International fax: +1 (641) 621-7730
www.vermeer.com

Vermeer Asia Pacific
48 Toh Guan Road East
#01-105 Enterprise Hub
Singapore 608586
Phone: +65 6516 9560
Fax: +65 6515 9218

Call toll-free 1-888-VERMEER
1-888-837-6337 (U.S.A. only)

Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information about machine specifications.

Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation.

Vermeer and the Vermeer logo are trademarks of Vermeer Manufacturing Company in the U.S. and / or other countries.

Kohler is a trademark of Kohler Co. Kubota is a trademark of Kubota, Ltd.

© 2010 Vermeer Corporation. All Rights Reserved.

Printed in the U.S.A.